


KA-30

全自動門框雙端打樁機

AUTOMATIC DOUBLE END DOOR FRAME TENONERS



- ◻ 最大加工長度: 2.5m-3m, 加工高度: 200mm
- ◻ 全油壓系統, 無任何震動字異動。
- ◻ 機檯採用高精度高性能線性滑軌及高精度滾珠螺桿, 長度採用數碼控制器, 精準左右移動。
- ◻ 機檯採用PLC控制器, 集中式控制屏操作容易, 全密封式安全符合CE安全規範。
- ◻ 左右機檯可在同一台機檯完成, 可同時加工左右兩端機檯, 加工速度快, 效率高。

- ◻ The machine max. working length is 2.5m-3m, and the max. working width is 200mm.
- ◻ Full hydraulic control system ensure does not vibration with working stability.
- ◻ Heavy rigid design with linear rail, ball screw with precision length setting by digital readout controller to left right move accurately.
- ◻ Electronic with PLC central control panel unit, can be easy to operate. All-enclosure safety to match CE standards.
- ◻ Double end tenoner can be done two end in a process at the same time, working with high speed. Raise the efficiency of labour.




右刀架
RIGHT CUTTER UNIT
90度及45度雙刀架採用油壓系統作動具高度穩定性
Hydraulic control of two cutter unit 90° and 45°, ensuring stability.



左刀架
LEFT CUTTER UNIT
90度及45度雙刀架採用油壓系統作動具高度穩定性
Hydraulic control of two cutter unit 90° and 45°, ensuring stability.



控制屏
CONTROL PANEL UNIT
可移動式控制屏, 集中式控制屏板, 附有數碼控制器可提供精準長度設定。
Movable and central control panel with electronic digital readout setting length standard.



採用高精度高性能線性滑軌及高精度滾珠螺桿
Heavy rigid design with linear rail, high precision setting ball screw.



NEW

KA-302S

全自動門框雙端打樁機

AUTOMATIC DOUBLE END DOOR FRAME TENONERS

全自動門框雙端打樁機, 增加了切膠密裝功能, 切膠後機檯自動回到料室內操作打樁加工。打樁加工完成後, 機檯會自動退料機檯, 避免發生安全隱患的危險。
The new automatic door frame double-end tenoning machine, increase the length of the cut set, cut off the conveyor belt automatic feed to the internal right tenon processing, tenon processing is completed, the conveyor will be automatically sent the material back, at one time the entire production process.

Specifications 規格表:

MODEL	型號	KA-30
Max. working length	加工長度	600-3000 mm
Max. working height	加工高度	82 mm
Max. working width	加工寬度	200 mm
Spindle motor	主軸馬力	7.5HPx4
Hydraulic pump motor	油壓幫浦馬力	3HPx1
Spindle diameter	主軸直徑	Ø40 mm
Spindle speed	主軸轉速	5000 rpm
Machine size(LxWxH)	機械尺寸	5500x1700x2050mm
Packing size(LxWxH)	裝箱尺寸	5650x1850x2250mm
Net weight	淨重	2500kgs
Gross weight	毛重	3000kgs

All specifications and design characteristics shown in this catalogue are subject to change without notice. 以上數值因不斷研發, 若有變更恕不另行通知。

Specifications 規格表:

MODEL	型號	KA-302S
Max. working length	加工長度	600-3000 mm
Max. working height	加工高度	35-90 mm
Max. working width	加工寬度	100-200 mm
Spindle motor	主軸馬力	10 HP
Hydraulic pump motor	油壓幫浦馬力	3 HP
Spindle diameter	主軸直徑	Ø40 mm
Spindle speed	主軸轉速	5000 rpm
Saw blade dia.	鋸片尺寸	16"
Saw motor	鋸片馬力	3 HP
Saw speed	鋸片轉速	3000 rpm
Conveyor motor	輸送帶	1/2 HP
Machine size(LxWxH)	機械尺寸	6200x2100x2300 mm
Packing size(LxWxH)	裝箱尺寸	6300x2300x2450 mm
Net weight	淨重	5400 kgs
Gross weight	毛重	6000 kgs

All specifications and design characteristics shown in this catalogue are subject to change without notice. 以上數值因不斷研發, 若有變更恕不另行通知。